

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

*SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006*

## **ACETONE R BULK**

Version 6.0

Print Date 18.03.2015

Revision date / valid from 12.08.2014

### **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### **1.1. Product identifier**

Trade name : ACETONE R BULK  
Substance name : acetone  
Index-No. : 606-001-00-8  
CAS-No. : 67-64-1  
EC-No. : 200-662-2  
Registration number : 01-2119471330-49-xxxx

#### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the Substance/Mixture : Identified use: See table in front of appendix for a complete overview of identified uses.  
Uses advised against : At this moment we have not identified any uses advised against

#### **1.3. Details of the supplier of the safety data sheet**

Company : Сердика офиси  
бул. Ситняково 48, ет. 10  
BG 1505 София, България  
Telephone : +359 2 926 56 00  
Telefax : +359 2 879 32 70  
E-mail address : info@brenntag.bg

#### **1.4. Emergency telephone number**

Emergency telephone number : National toxicology informational center  
Emergency medical aid Center "Pirogov"  
Director of National toxicology information center: Dr. Evgenia Stankova  
Director of National clinical toxicology center: prof.Aneta Hubenova  
Emergency phone number: +359 2 9154 409 / +359 9154 346  
Fax: +359 2 9154 409  
E-mail: poison\_centre@mail.orbitel.bg  
<http://www.pirogov.net>

### **SECTION 2: Hazards identification**

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

REGULATION (EC) No 1272/2008			
Hazard class	Hazard category	Target Organs	Hazard statements
Flammable liquids	Category 2	---	H225
Serious eye damage/eye irritation	Category 2	---	H319
Specific target organ toxicity - single exposure	Category 3	---	H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### Classification according to EU Directives 67/548/EEC or 1999/45/EC

Directive 67/548/EEC or 1999/45/EC	
Hazard symbol / Category of danger	Risk phrases
Highly flammable (F)	R11
Irritant (Xi)	R36
	R66
	R67

For the full text of the R-phrases mentioned in this Section, see Section 16.

#### Most important adverse effects

Human Health : See section 11 for toxicological information.  
Physical and chemical hazards : See section 9 for physicochemical information.  
Potential environmental effects : See section 12 for environmental information.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No 1272/2008

Hazard symbols :



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

Signal word	:	Danger	
Hazard statements	:	H225 H319 H336	Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements			
Prevention	:	P210  P233 P240  P243  P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response	:	P303 + P361 + P353  P304 + P340	IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Storage	:	P403 + P235	Store in a well-ventilated place. Keep cool.

### Additional Labelling:

EUH066 Repeated exposure may cause skin dryness or cracking.

### Hazardous components which must be listed on the label:

- acetone

### 2.3. Other hazards

For Results of PBT and vPvB assessment see section 12.5.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Hazardous components	Amount [%]	Classification (REGULATION (EC) No 1272/2008)	Classification (67/548/EEC)
----------------------	------------	--	--------------------------------

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapgui\WWI\graphics\ConnectingChemistry.jpg }

{ error: graphic file not found: C:\Program Files  
(x86)\SAP\FrontEnd\sapgui\WWI\graphics\brenntag.bmp }

## ACETONE R BULK

		Hazard class / Hazard category	Hazard statements	
<b>acetone</b>				
Index-No.	: 606-001-00-8	Flam. Liq.2	H225	Highly flammable;
CAS-No.	: 67-64-1	Eye Irrit.2	H319	F; R11
EC-No.	: 200-662-2	STOT SE3	H336	Irritant; Xi; R36
Registration	: 01-2119471330-49-xxxx <= 100			R66 R67

For the full text of the R-phrases mentioned in this Section, see Section 16.  
For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- General advice : Remove from exposure, lie down. Take off all contaminated clothing immediately.
- If inhaled : Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water. Call a physician if irritation persists.
- In case of eye contact : Consult an eye specialist immediately. Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
- If swallowed : Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. If swallowed, do not induce vomiting - seek medical advice. If a person vomits when lying on his back, place him in the recovery position.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms : acidosis, Control the alkaline reserve, Shortness of breath, Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. See Section 11 for more detailed information on health effects and symptoms.
- Effects : Aspiration hazard if swallowed - can enter lungs and cause damage. Aspiration may cause pulmonary oedema and pneumonitis.

### 4.3. Indication of any immediate medical attention and special treatment needed

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

Treatment : Treat symptomatically.Later control for pneumonia and lung oedema.In case of shortness of breath, give oxygen.Artificial respiration and/or oxygen may be necessary.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Unsuitable extinguishing media : High volume water jet

#### **5.2. Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Flash back possible over considerable distance. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, Carbon dioxide (CO<sub>2</sub>)

#### **5.3. Advice for firefighters**

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.Wear appropriate body protection (full protective suit)  
Further information : Cool closed containers exposed to fire with water spray.Heating will cause a pressure rise - with risk of bursting.Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment. Keep away unprotected persons. Provide adequate ventilation. Keep away from heat and sources of ignition. Avoid contact with skin and eyes. Do not breathe vapours or spray mist. For personal protection see section 8.

#### **6.2. Environmental precautions**

Environmental precautions : Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration. If the product contaminates rivers and lakes or drains inform respective authorities.

#### **6.3. Methods and materials for containment and cleaning up**

Methods and materials for containment and cleaning : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

up vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Further information : Treat recovered material as described in the section "Disposal considerations".

### **6.4. Reference to other sections**

For personal protection see section 8.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

Advice on safe handling : Keep container tightly closed. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with the skin and the eyes. Do not breathe vapours or spray mist. Emergency eye wash fountains and emergency showers should be available in the immediate vicinity.

Hygiene measures : Keep away from food, drink and animal feedingstuffs. Smoking, eating and drinking should be prohibited in the application area. Wash hands before breaks and at the end of workday. Take off all contaminated clothing immediately. Avoid contact with the skin and the eyes. Do not breathe vapours or spray mist.

### **7.2. Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Keep in an area equipped with solvent resistant flooring. Suitable materials for containers: Steel; Stainless steel; Unsuitable materials for containers: Plastic material; Copper

Advice on protection against fire and explosion : Combustible liquid. Keep away from sources of ignition - No smoking. Use only explosion-proof equipment. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Take measures to prevent the build up of electrostatic charge. Use only in an area containing explosion proof equipment.

Further information on storage conditions : Keep tightly closed in a dry and cool place. Keep away from direct sunlight. Keep away from heat. Keep in a well-ventilated place.

Advice on common storage : Keep away from food, drink and animal feedingstuffs. Incompatible with oxidizing agents.

German storage class : 3 Flammable Liquids

### **7.3. Specific end use(s)**

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

Specific use(s) : Identified use: See table in front of appendix for a complete overview of identified uses.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Component:	acetone	CAS-No. 67-64-1
<b>Derived No Effect Level (DNEL)/Derived Minimal Effect Level (DMEL)</b>		

DNEL  
Workers, Systemic effects, Skin contact  
Long-term exposition : 186 mg/kg bw/day

DNEL  
Workers, Systemic effects, Inhalation  
Long-term exposition : 1210 mg/m3

DNEL  
Workers, Local effects, Inhalation  
Short-term exposition : 2420 mg/m3

DNEL  
Consumers, Systemic effects, Skin contact  
Long-term exposition : 62 mg/kg bw/day

DNEL  
Consumers, Systemic effects, Inhalation  
Long-term exposition : 200 mg/m3

DNEL  
Consumers, Systemic effects, Ingestion  
Long-term exposition : 62 mg/kg bw/day

<b>Predicted No Effect Concentration (PNEC)</b>		
Fresh water	:	10,6 mg/l
Marine water	:	1,06 mg/l
Intermittent releases	:	21 mg/l
Sewage treatment plant (STP)	:	100 mg/l
Fresh water sediment	:	30,4 mg/kg

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

Marine sediment : 3,04 mg/kg  
Soil : 29,5 mg/kg

### Other Occupational Exposure Limit Values

TRGS 900, AGW:  
500 ppm, 1.200 mg/m<sup>3</sup>, (2)

EU ELV, Time Weighted Average (TWA):  
500 ppm, 1.210 mg/m<sup>3</sup>  
Indicative

### Biological Exposure Indices

DE BAT, acetone, Urine  
80 mg/l, Sampling time: End of shift.

## 8.2. Exposure controls

### Appropriate engineering controls

Refer to protective measures listed in sections 7 and 8.

### Personal protective equipment

#### *Respiratory protection*

Advice : Required, if exposure limit is exceeded (e.g. OEL).  
In case of insufficient ventilation, wear suitable respiratory  
equipment.  
Breathing apparatus with filter.  
Recommended Filter type:AX

#### *Hand protection*

Advice : Wear suitable gloves.  
Solvent-resistant gloves  
Protective gloves should be replaced at first signs of wear.

Advice : The following materials are suitable:

Material : butyl-rubber  
Break through time :  $\geq 8$  h  
Glove thickness : 0,5 mm  
Guideline : DIN EN 374

Advice : Unsuitable materials:



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

Material : natural latex

Advice : Unsuitable materials:

Material : polychloroprene

Advice : Unsuitable materials:

Material : PVC

### *Eye protection*

Advice : Tightly fitting safety goggles

### *Skin and body protection*

Advice : Solvent resistant protective clothing

### **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.  
Avoid subsoil penetration.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

Form : liquid

Colour : colourless

Odour : sweet

Odour Threshold : ca. 13 ppm

pH : 5 - 6 (10 g/l; 20 °C)

Melting point/range : -94,7 °C

Boiling point/boiling range : 55,8 - 56,6 °C

Flash point : -18 °C (closed cup)

Evaporation rate : no data available

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

Flammability (solid, gas)	: Highly flammable.
Upper explosion limit	: 13,0 %(V)
Lower explosion limit	: 2,1 %(V)
Vapour pressure	: 240 hPa (20 °C) 800 hPa (50 °C)
Relative vapour density	: 2,0
Density	: 0,791 g/cm <sup>3</sup> (20 °C)
Water solubility	: completely miscible
Partition coefficient: n-octanol/water	: log Kow -0,24 (20 °C) (measured)
Auto-ignition temperature	: 465 °C
Thermal decomposition	: no data available
Viscosity, dynamic	: 0,33 mPa.s (20 °C)
Explosivity	: Formation of explosive air/vapour mixtures is possible.
Oxidizing properties	: not oxidising

### **9.2. Other information**

Molecular weight	: 58,09 g/mol
Refractive index	: 1,358 - 1,359

## **SECTION 10: Stability and reactivity**

### **10.1. Reactivity**

Advice : Combustibles vapours may form with air. Take measures to prevent the build up of electrostatic charge.  
Vapours are heavier than air and may spread along floors.

### **10.2. Chemical stability**

Advice : Stable under normal conditions.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 10.3. Possibility of hazardous reactions

Hazardous reactions : Possible formation of peroxide.

### 10.4. Conditions to avoid

Conditions to avoid : Keep away from heat and sources of ignition.

### 10.5. Incompatible materials

Materials to avoid : strong reducing agents, Oxidizing agents, Halogenated compounds, Alkali metals, Ethanolamine, Hydrogen peroxide, Attacks certain plastics and rubbers.

### 10.6. Hazardous decomposition products

Hazardous decomposition products : Under fire conditions: Carbon monoxide, Carbon dioxide (CO<sub>2</sub>)

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Component:	acetone	CAS-No. 67-64-1
<b>Acute toxicity</b>		
<b>Oral</b>		
LD50	:	5800 mg/kg (rat) (OECD Test Guideline 401) Based on available data, the classification criteria are not met., Cause pain in mouth and throat, nausea, vomiting, dizziness, headache and risk of unconsciousness.
<b>Inhalation</b>		
LC50	:	ca. 76 mg/l (rat; 4 h) Based on available data, the classification criteria are not met. May cause pain in nose and throat, nausea, dizziness, headache, deteriorate reactivity and at high concentration unconsciousness.
<b>Dermal</b>		
LD50	:	> 15800 mg/kg (rabbit) Based on available data, the classification criteria are not met.
<b>Irritation</b>		

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

### **Skin**

Result : No skin irritation (guinea pig)  
Based on available data, the classification criteria are not met.  
  
Repeated exposure may cause skin dryness or cracking.

### **Eyes**

Result : Irritating to eyes. (rabbit) (OECD Test Guideline 405)  
May cause corneal damage.

### **Sensitisation**

Result : not sensitizing (guinea pig) (OECD Test Guideline 406)  
Based on available data, the classification criteria are not met.

### **CMR effects**

#### **CMR Properties**

Carcinogenicity : Animal testing did not show any carcinogenic effects.  
  
Mutagenicity : Tests on bacterial or mammalian cell cultures did not show  
mutagenic effects.  
  
Reproductive toxicity : Animal testing did not show any effects on fertility.

#### **Carcinogenicity**

(negative, mouse)  
(Dermal)  
Tests on animals showed no cancerogenic effects.

#### **Genotoxicity in vitro**

negative (Chromosome aberration test in vitro) (OECD Test  
Guideline 473)  
In vitro tests did not show mutagenic effects

negative (In vitro gene mutation study in mammalian cells) (OECD  
Test Guideline 476)

negative (In vitro gene mutation study in bacteria) (OECD Test  
Guideline 471)

#### **Genotoxicity in vivo**

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

negative (In vivo micronucleus test; mouse)  
In vivo tests did not show mutagenic effects

### Teratogenicity

(Fertility/early embryonic development; rat)  
(OECD Test Guideline 414)  
negative  
Based on available data, the classification criteria are not met.

### Specific Target Organ Toxicity

#### Single exposure

remark : May cause drowsiness or dizziness.

#### Repeated exposure

remark : Based on available data, the classification criteria are not met.

### Other toxic properties

#### Repeated dose toxicity

NOAEL : 900 mg/kg bw/day  
(rat)  
(Oral; 90-day)

NOAEC : 22500 mg/m<sup>3</sup>  
(rat)  
(Inhalation)

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### Further information

Experience with human exposure : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Chronic exposure may cause dermatitis.  
Chronic inhalation causes tiredness, headache and rhinitis.

## SECTION 12: Ecological information

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 12.1. Toxicity

Component:	acetone	CAS-No. 67-64-1
<b>Acute toxicity</b>		
<b>Fish</b>		
LC50	:	5540 mg/l (Oncorhynchus mykiss; 96 h)
LC50	:	11000 mg/l (Alburnus alburnus; 96 h)
<b>Toxicity to daphnia and other aquatic invertebrates</b>		
LC50	:	8800 mg/l (Daphnia magna; 48 h)
<b>algae</b>		
NOEC	:	430 mg/l (algae; 96 h)
<b>Bacteria</b>		
		1000 mg/l (activated sludge; 0,5 h) (Toxicity to bacteria; OECD Test Guideline 209)
<b>Chronic toxicity</b>		
<b>Aquatic invertebrates</b>		
NOEC	:	2212 mg/l (Daphnia pulex (Water flea); 28 d) (Reproductive toxicity)

### 12.2. Persistence and degradability

Component:	acetone	CAS-No. 67-64-1
<b>Persistence and degradability</b>		
<b>Persistence</b>		
Result	:	decomposition by hydrolysis.
<b>Biodegradability</b>		

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

Result : 91 % (Exposure Time: 28 d)(OECD 301 B)  
Readily biodegradable

### 12.3. Bioaccumulative potential

<b>Component:</b>	<b>acetone</b>	<b>CAS-No.</b>
		<b>67-64-1</b>

#### Bioaccumulation

Result : log Kow -0,24  
BCF: < 10  
Does not bioaccumulate.

### 12.4. Mobility in soil

<b>Component:</b>	<b>acetone</b>	<b>CAS-No.</b>
		<b>67-64-1</b>

#### Mobility

: The product evaporates readily.

### 12.5. Results of PBT and vPvB assessment

<b>Component:</b>	<b>acetone</b>	<b>CAS-No.</b>
		<b>67-64-1</b>

#### Results of PBT and vPvB assessment

Result : This substance is not considered to be persistent, bioaccumulating nor toxic (PBT)., This substance is not considered to be very persistent nor very bioaccumulating (vPvB).

### 12.6. Other adverse effects

<b>Component:</b>	<b>acetone</b>	<b>CAS-No.</b>
		<b>67-64-1</b>

#### Biochemical Oxygen Demand (BOD)

Result : 1900 mg/g (Incubation time: 5 d)

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### Chemical Oxygen Demand (COD)

Result : 2100 mg/g

### Additional ecological information

Result : Do not flush into surface water or sanitary sewer system.  
Avoid subsoil penetration.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product : Disposal together with normal waste is not allowed. Special disposal required according to local regulations. Do not let product enter drains. Contact waste disposal services.

Contaminated packaging : Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning. Do not burn, or use a cutting torch on, the empty drum. Risk of explosion.

European Waste Catalogue Number : No waste code according to the European Waste Catalogue can be assigned for this product, as the intended use dictates the assignment. The waste code is established in consultation with the regional waste disposer.

## SECTION 14: Transport information

### 14.1. UN number

1090

### 14.2. UN proper shipping name

ADR : ACETONE  
RID : ACETONE  
IMDG : ACETONE

### 14.3. Transport hazard class(es)

ADR-Class : 3  
(Labels; Classification Code; Hazard identification No; Tunnel restriction code) 3; F1; 33; (D/E)  
RID-Class : 3  
(Labels; Classification Code; Hazard identification No) 3; F1; 33  
IMDG-Class : 3



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

(Labels; EmS)

3; F-E, S-D

### 14.4. Packaging group

ADR : II  
RID : II  
IMDG : II

### 14.5. Environmental hazards

Labeling according to 5.2.1.8 ADR : no  
Labeling according to 5.2.1.8 RID : no  
Labeling according to 5.2.1.6.3 IMDG : no  
Classification as environmentally  
hazardous according to 2.9.3 IMDG : no  
Classified as "P" according to 2.10 IMDG : no

### 14.6. Special precautions for user

Note : not applicable

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IMDG : Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

WGK (DE) : acetone: WGK Identification Number: 6; WGK:1; slightly water  
endangering; Classification source is Annex 2.

#### acetone

EU. REACH, Annex XVII, Marketing and Use Restrictions  
(Regulation 1907/2006/EC)  
Listed Point Nos.: 40

EU. Regulation 273/2004, Drug Precursors, Category 3  
Scheduled substance Combined Nomenclature (CN)  
denomination. Scheduled substance Combined Nomenclature  
(CN) code: 2914 11 00

#### Notification status

##### acetone:

Regulatory List  
AICS

Notification  
YES

Notification number

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

DSL	YES	
INV (CN)	YES	
ENCS (JP)	YES	(2)-542
ISHL (JP)	YES	(2)-542
NZ CLSC	YES	
TSCA	YES	
EINECS	YES	200-662-2
KECI (KR)	YES	KE-29367
PICCS (PH)	YES	
IECSC	YES	

### 15.2. Chemical Safety Assessment

Currently we do not have any information from our supplier about this.  
A Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: Other information

### Full text of R-phrases referred to under sections 2 and 3.

R11	Highly flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

### Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

### Further information

Key literature references : Supplier information and data from the "Database of registered substances" of the European Chemicals Agency (ECHA) were used to create this safety data sheet.

Other information : The information provided in this Safety Data Sheet is correct to our knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements and is not to be considered as a warranty or quality specification and does not constitute a legal relationship. The information contained in this Safety Data Sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text

|| Indicates updated section.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

No.	Short title	Main User Group (SU)	Sector of Use (SU)	Product Category (PC)	Process Category (PROC)	Environmental Release Category (ERC)	Article Category (AC)	Specified
1	Manufacture of substance	3	NA	NA	1, 2, 3, 4, 5, 6, 8a, 8b, 9, 10, 14, 15	1, 2, 4, 6a	NA	ES7668
2	Rubber production and processing	3	NA	NA	1, 2, 3, 4, 5, 6, 7, 8a, 8b, 9, 10, 13, 14	6d	NA	ES7680
3	Polymer production	3	NA	NA	1, 2, 3, 4, 5, 6, 8a, 8b, 9, 10, 13, 14, 15	6d	NA	ES7682
4	Polymer production	22	NA	NA	1, 2, 8a, 8b, 9, 14	8a, 8c, 8d, 8f	NA	ES7741
5	Polymer processing	3	NA	NA	1, 2, 3, 4, 5, 6, 8a, 8b, 9, 10, 13, 14, 15	6d	NA	ES7684
6	Polymer processing	22	NA	NA	1, 2, 8a, 8b, 9, 14	8a, 8c, 8d, 8f	NA	ES7743
7	Uses in coatings	3	NA	NA	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 13, 15, 19	4	NA	ES7672
8	Uses in coatings	21	NA	1, 4, 9a, 9b, 9c, 15, 24, 31	NA	8a, 8c, 8d, 8f	NA	ES8830
9	Uses in coatings	22	NA	NA	1, 2, 3, 4, 5, 8a, 8b, 9, 10, 11, 13, 15, 19	8a, 8c, 8d, 8f	NA	ES7737
10	Use in Cleaning Agents	3	NA	NA	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 13, 19	4	NA	ES7686
11	Use in Cleaning Agents	21	NA	3, 4, 9a, 9b, 9c, 24, 35, 38	NA	8a, 8d	NA	ES8831
12	Use in Cleaning Agents	22	NA	NA	1, 2, 3, 4, 5, 8a, 8b, 9, 10, 11, 13, 19	8a, 8d	NA	ES7745
13	Use as binders and release agents	3	NA	NA	1, 2, 3, 4, 5, 6, 7, 8a, 8b, 9, 10, 13	5	NA	ES7678
14	Use as binders and release agents	22	NA	NA	1, 2, 3, 4, 5, 6, 8a, 8b, 9, 10, 11	8a, 8b, 8c, 8d, 8e, 8f	NA	ES7739
15	Use in agrochemicals	22	NA	NA	1, 2, 4, 8a, 8b, 11, 13, 19	8a, 8d	NA	ES7749

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

16	Use in laboratories	3	NA	NA	10, 15, 19	4	NA	ES7670
17	Use in laboratories	22	NA	NA	10, 15, 19	8a	NA	ES7735
18	Use as blowing agents	3	NA	NA	1, 2, 3, 8b, 9, 12	4, 10a	NA	ES7690
19	Use in de-icing and anti-icing applications	21	NA	4	NA	8d	NA	ES8832
20	Use in de-icing and anti-icing applications	22	NA	NA	1, 2, 8b, 11, 19	8d	NA	ES7751
21	Use in Oil and Gas field drilling and production operations	3	NA	NA	1, 2, 3, 4, 8a, 8b	4	NA	ES7688
22	Use in Oil and Gas field drilling and production operations	22	NA	NA	1, 2, 3, 4, 8a, 8b	8d	NA	ES7747
23	Explosives manufacture & use	22	NA	NA	1, 3, 5, 8a, 8b	8d	NA	ES7753

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 1: Manufacture of substance

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC6: Calendaring operations</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation</p> <p>PROC15: Use as laboratory reagent</p>
Environmental Release Categories	<p>ERC1: Manufacture of substances</p> <p>ERC2: Formulation of preparations</p> <p>ERC4: Industrial use of processing aids in processes and products, not becoming part of articles</p> <p>ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)</p>

#### 2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC2, ERC4, ERC6a

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

#### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC14, PROC15

Product characteristics	Concentration of the	Covers percentage substance in the product up to
-------------------------	----------------------	--

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Substance in Mixture/Article	100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3)	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2, PROC14, PROC15	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3, PROC4	---	Inhalation	100ppm	0,20
PROC4, PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC5, PROC6, PROC8a, PROC10	---	Inhalation	250ppm	0,50
PROC5, PROC8a	---	Dermal	13,71mg/kg/day	0,07
PROC6, PROC10	---	Dermal	27,43mg/kg/day	0,15
PROC8b	---	Inhalation	150ppm	0,30
PROC8b	---	Dermal	6,86mg/kg/day	0,037
PROC9	---	Inhalation	200ppm	0,40
PROC14, PROC15	---	Dermal	0,34mg/kg/day	0,00

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template  
(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### **Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 2: Rubber production and processing

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure          PROC2: Use in closed, continuous process with occasional controlled exposure          PROC3: Use in closed batch process (synthesis or formulation)          PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises          PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)          PROC6: Calendering operations          PROC7: Industrial spraying          PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities          PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities          PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)          PROC10: Roller application or brushing          PROC13: Treatment of articles by dipping and pouring          PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation</p>
Environmental Release Categories	ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

### 2.1 Contributing scenario controlling environmental exposure for: ERC6a, ERC6b, ERC6c, ERC6d

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of	liquid



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	use)	
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3)	
	Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC7)	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
	If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A filter or better.(PROC7)	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2, PROC14	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3, PROC4	---	Inhalation	100ppm	0,20
PROC4, PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC5, PROC6, PROC8a, PROC10, PROC13	---	Inhalation	250ppm	0,50
PROC5, PROC8a	---	Dermal	13,71mg/kg/day	0,07
PROC6, PROC10	---	Dermal	27,43mg/kg/day	0,15
PROC7	with local exhaust ventilation, (95% efficiency)	Inhalation	25ppm	0,05
PROC7	---	Dermal	2,14mg/kg/day	0,01
PROC7	Outdoor use., 30% efficiency	Inhalation	350ppm	0,70

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

PROC7	---	Dermal	42,86mg/kg/day	0,23
PROC7	half mask	Inhalation	50ppm	0,10
PROC8b	---	Inhalation	150ppm	0,30
PROC8b	---	Dermal	6,86mg/kg/day	0,037
PROC9	---	Inhalation	200ppm	0,40
PROC13	---	Dermal	13,71 mg/kg/day	0,074
PROC14	---	Dermal	0,34mg/kg/day	0,00

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 3: Polymer production

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC6: Calendering operations</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation</p> <p>PROC15: Use as laboratory reagent</p>
Environmental Release Categories	ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

### 2.1 Contributing scenario controlling environmental exposure for: ERC6d

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of	liquid

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	use)	
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3)	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2, PROC14, PROC15	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3, PROC4	---	Inhalation	100ppm	0,20
PROC4, PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC5, PROC6, PROC8a, PROC10, PROC13	---	Inhalation	250ppm	0,50
PROC5, PROC8a	---	Dermal	13,71mg/kg/day	0,07
PROC6, PROC10	---	Dermal	27,43mg/kg/day	0,15
PROC8b	---	Inhalation	150ppm	0,30
PROC8b	---	Dermal	6,86mg/kg/day	0,037
PROC9	---	Inhalation	200ppm	0,40
PROC13	---	Dermal	13,71mg/kg/day	0,074
PROC14, PROC15	---	Dermal	0,34mg/kg/day	0,00

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Environment

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template  
(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### **Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 4: Polymer production

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix ERC8d: Wide dispersive outdoor use of processing aids in open systems ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

### 2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8c, ERC8d, ERC8f

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC8a, PROC8b, PROC9, PROC14

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion	Locate bulk storage outdoors.	

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

from source towards the worker	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2)
	Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC8a)
	or Avoid carrying out operation for more than 4 hours.(PROC8a)
	Ensure material transfers are under containment or extract ventilation. or Avoid carrying out operation for more than 4 hours.(PROC14)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC14	---	Dermal	0,34mg/kg/day	0,002
PROC2	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC8a, PROC14	with local exhaust ventilation, 80% efficiency	Inhalation	100ppm	0,20
PROC8a	---	Dermal	0,14mg/kg/day	0,001
PROC8a	Outdoor use., 30% efficiency	Inhalation	350ppm	0,70
PROC8a	---	Dermal	13,71mg/kg/day	0,07
PROC8a	during 1 - 4 hours	Inhalation	300ppm	0,60
PROC8b, PROC9	---	Inhalation	250ppm	0,50
PROC8b, PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC14	during 1 - 4 hours	Inhalation	300ppm	0,002

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template  
(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### **Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 5: Polymer processing

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC6: Calendering operations</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation</p> <p>PROC15: Use as laboratory reagent</p>
Environmental Release Categories	ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

### 2.1 Contributing scenario controlling environmental exposure for: ERC6d

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of	liquid

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	use)	
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3)	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2, PROC14, PROC15	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3, PROC4	---	Inhalation	100ppm	0,20
PROC4, PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC5, PROC8a	---	Dermal	13,71mg/kg/day	0,07
PROC6, PROC10	---	Dermal	27,43mg/kg/day	0,15
PROC5, PROC6, PROC8a, PROC10, PROC13	---	Inhalation	250ppm	0,50
PROC8b	---	Inhalation	150ppm	0,30
PROC8b	---	Dermal	6,86mg/kg/day	0,037
PROC9	---	Inhalation	200ppm	0,40
PROC13	---	Dermal	13,71mg/kg/day	0,074
PROC14, PROC15	---	Dermal	0,34mg/kg/day	0,00

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Environment

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### **Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 6: Polymer processing

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC14: Production of preparations or articles by tableting, compression, extrusion, pelettisation
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix ERC8d: Wide dispersive outdoor use of processing aids in open systems ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

### 2.1 Contributing scenario controlling environmental exposure for: ERC8a

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC8a, PROC8b, PROC9, PROC14

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion	Locate bulk storage outdoors.	

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

from source towards the worker	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2)
	Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC8a)
	or Avoid carrying out operation for more than 4 hours.(PROC8a)
	Ensure material transfers are under containment or extract ventilation. or Avoid carrying out operation for more than 4 hours.(PROC14)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC14	---	Dermal	0,34mg/kg/day	0,002
PROC2	---	Inhalation	20ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC8a, PROC14	with local exhaust ventilation, 80% efficiency	Inhalation	100ppm	0,20
PROC8a	---	Dermal	0,14mg/kg/day	0,001
PROC8a	Outdoor use., 30% efficiency	Inhalation	350ppm	0,70
PROC8a	---	Dermal	13,71mg/kg/day	0,07
PROC8a, PROC14	during 1 - 4 hours	Inhalation	300ppm	0,60
PROC8b, PROC9	---	Inhalation	250ppm	0,50
PROC8b, PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC14	---	Dermal	3,43mg/kg/day	0,02

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template  
(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### **Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 7: Uses in coatings

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC15: Use as laboratory reagent</p> <p>PROC19: Hand-mixing with intimate contact and only PPE available</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

### 2.1 Contributing scenario controlling environmental exposure for: ERC4

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Charcoal adsorbers, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC19

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of	liquid

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	use)	
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3)	
	Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC7)	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
	If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A filter or better.(PROC7)	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

##### ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2, PROC15	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3, PROC4	---	Inhalation	100ppm	0,20
PROC4, PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC5, PROC8a, PROC10, PROC13, PROC19	---	Inhalation	250ppm	0,50
PROC5, PROC8a, PROC13	---	Dermal	13,71mg/kg/day	0,07
PROC7	with local exhaust ventilation, (95% efficiency)	Inhalation	25ppm	0,05
PROC7	---	Dermal	2,14mg/kg/day	0,01
PROC7	Outdoor use., 30% efficiency	Inhalation	350ppm	0,70
PROC7	---	Dermal	42,86mg/kg/day	0,23



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

PROC7	half mask	Inhalation	50ppm	0,10
PROC8b	---	Inhalation	150ppm	0,30
PROC8b	---	Dermal	6,86mg/kg/day	0,037
PROC9	---	Inhalation	200ppm	0,40
PROC10	---	Dermal	27,43mg/kg/day	0,15
PROC15	---	Dermal	0,34mg/kg/day	0,00
PROC19	with gloves	Dermal	28,29mg/kg/day	0,15

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 8: Uses in coatings

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC1: Adhesives, sealants PC4: Anti-freeze and de-icing products PC9a: Coatings and paints, thinners, paint removers PC9b: Fillers, putties, plasters, modelling clay PC9c: Finger paints PC15: Non-metal-surface treatment products PC24: Lubricants, greases, release products PC31: Polishes and wax blends
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix ERC8d: Wide dispersive outdoor use of processing aids in open systems ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

#### 2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8c, ERC8d, ERC8f

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

#### 2.2 Contributing scenario controlling consumer exposure for: PC1: Glues, hobby use

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	9 g
Frequency and duration of use	Exposure duration	< 4 h
	Frequency of use	< 365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

risk management		
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.3 Contributing scenario controlling consumer exposure for: PC1: Glues DIY-use (carpet glue, tile glue, wood parquet glue)</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	6390 g
Frequency and duration of use	Exposure duration	6 h
	Frequency of use	1 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 110 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.4 Contributing scenario controlling consumer exposure for: PC1: Glue from spray</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 30%
	Physical Form (at time of use)	spray aerosol
Amount used	Amount used per event	85,05 g
Frequency and duration of use	Exposure duration	4 h
	Frequency of use	6 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.5 Contributing scenario controlling consumer exposure for: PC4: Washing car window</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 1 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	0,5 g
Frequency and duration of use	Exposure duration	0,02 h
	Frequency of use	365 days/year

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 6600 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use in a one car garage (34 m3) under typical ventilation.	
<b>2.6 Contributing scenario controlling consumer exposure for: PC4: Pouring into radiator</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	2000 g
Frequency and duration of use	Exposure duration	0,17 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use in a one car garage (34 m3) under typical ventilation.	
<b>2.7 Contributing scenario controlling consumer exposure for: PC4: Lock de-icer</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	4 g
Frequency and duration of use	Exposure duration	0,25 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 214,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use in a one car garage (34 m3) under typical ventilation.	
<b>2.8 Contributing scenario controlling consumer exposure for: PC9a: Waterborne latex wall paint</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 1,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	2760 g
Frequency and duration of use	Exposure duration	2,2 h

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Frequency of use	4 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.9 Contributing scenario controlling consumer exposure for: PC9a: Solvent rich, high solid, water borne paint, PC15: Solvent rich, high solid, water borne paint</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 27,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	744 g
Frequency and duration of use	Exposure duration	2,2 h
	Frequency of use	6 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 482,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.10 Contributing scenario controlling consumer exposure for: PC9a: Aerosol spray can, PC15: Aerosol spray can</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	spray aerosol
Amount used	Amount used per event	215 g
Frequency and duration of use	Exposure duration	0,33 h
	Frequency of use	2 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 6600 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use in a one car garage (34 m3) under typical ventilation.	
<b>2.11 Contributing scenario controlling consumer exposure for: PC9a: Removers (paint-, glue-, wall paper-, sealant-remover), PC15: Removers (paint-, glue-, wall paper-, sealant remover)</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Vapour pressure	240 hPa
Amount used	Amount used per event	491 g
Frequency and duration of use	Exposure duration	2 h
	Frequency of use	3 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.12 Contributing scenario controlling consumer exposure for: PC9b: Fillers and putty</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	85 g
Frequency and duration of use	Exposure duration	4 h
	Frequency of use	12 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.13 Contributing scenario controlling consumer exposure for: PC9b: Plasters and floor equalizers</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	13800 g
Frequency and duration of use	Exposure duration	2 h
	Frequency of use	12 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.14 Contributing scenario controlling consumer exposure for: PC9c: Finger paints</b>		
Product characteristics	Concentration of the	Covers concentrations up to 50%

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Substance in Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	1,35 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 254,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	Avoid using at a product concentration greater than 5%

### 2.15 Contributing scenario controlling consumer exposure for: PC24: Sprays

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	spray aerosol
Amount used	Amount used per event	73 g
Frequency and duration of use	Exposure duration	0,17 h
	Frequency of use	6 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	

### 2.16 Contributing scenario controlling consumer exposure for: PC31: Polishes, spray (furniture, shoes)

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	142 g
Frequency and duration of use	Exposure duration	1,23 h
	Frequency of use	29 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm <sup>2</sup>
Other given operational	Room size	20 m3

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

conditions affecting consumers  
exposure

Covers use under typical household ventilation., Covers use at ambient  
temperatures.

### **3. Exposure estimation and reference to its source**

#### **Environment**

No information available.

#### **Consumers**

#### **Consumers**

No exposure assessment presented for human health.

### **4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

#### **Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### **Health**

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Risk characterization ratios (RCRs) were calculated by comparing the predicted exposure levels with the corresponding DNELs (derived no effect levels) ( $RCR = \text{exposure level}/\text{DNEL}$ )



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 9: Uses in coatings

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC15: Use as laboratory reagent</p> <p>PROC19: Hand-mixing with intimate contact and only PPE available</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p> <p>ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix</p>

### 2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8c, ERC6d, ERC8f

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC15, PROC19

Product characteristics	Concentration of the Substance in	Covers percentage substance in the product up to 100 % (unless stated differently).
-------------------------	-----------------------------------	---

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3)	
	Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC5, PROC8a)	
	or Avoid carrying out operation for more than 4 hours.(PROC5, PROC8a)	
	Ensure material transfers are under containment or extract ventilation. or Limit the substance content in the mixture to 25 %.(PROC10)	
	or Avoid carrying out operation for more than 4 hours.(PROC10)	
	Ensure material transfers are under containment or extract ventilation. or Limit the substance content in the mixture to 25 %. Ensure operation is undertaken outdoors. Avoid carrying out operation for more than 4 hours.(PROC11)	
	or Avoid carrying out operation for more than 1 hour.(PROC11)	
	Avoid carrying out operation for more than 1 hour.(PROC19)	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
	If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A filter or better.(PROC11)	
	If above technical/organisational control measures are not feasible, then adopt following PPE: Limit the substance content in the mixture to 25 %. Wear suitable gloves tested to EN374.(PROC19)	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3,	---	Dermal	0,34mg/kg/day	0,002

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

PROC15				
PROC2, PROC15	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3	---	Inhalation	100ppm	0,20
PROC4, PROC8b, PROC9, PROC13	---	Inhalation	250ppm	0,50
PROC4, PROC8b, PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC5	---	Dermal	0,07mg/kg/day	0,00
PROC5, PROC8a	Outdoor use., 30% efficiency	Inhalation	350ppm	0,70
PROC5, PROC8a, PROC13	---	Dermal	13,71mg/kg/day	0,07
PROC5, PROC8a	during 1 - 4 hours	Inhalation	300ppm	0,60
PROC8a	---	Dermal	0,14mg/kg/day	0,001
PROC10	---	Dermal	1,37mg/kg/day	0,007
PROC11	with local exhaust ventilation, 80% efficiency	Inhalation	200ppm	0,40
PROC11	---	Dermal	2,14mg/kg/day	0,01
PROC11	during 1 - 4 hours, Concentration of substance in product: 5% - 25%, Outdoor use., 30% efficiency	Inhalation	252ppm	0,50
PROC11	Concentration of substance in product: 5% - 25%	Dermal	64,28mg/kg/day	0,35
PROC11	---	Dermal	107,14mg/kg/day	0,58
PROC19	Concentration of substance in product: 5% - 25%, with gloves	Dermal	16,97mg/kg/day	0,09
PROC5, PROC8a, PROC10	with local exhaust ventilation, 80% efficiency	Inhalation	100ppm	0,20
PROC11	half mask	Inhalation	100ppm	0,20
PROC19	Concentration of substance in product: 5% - 25%	Inhalation	300ppm	0,60

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Environment

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### **Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 10: Use in Cleaning Agents

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC19: Hand-mixing with intimate contact and only PPE available</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

### 2.1 Contributing scenario controlling environmental exposure for: ERC4

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC19

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3)	
	Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC7)	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
	If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A filter or better.(PROC7)	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3, PROC4	---	Inhalation	100ppm	0,20
PROC4, PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC5, PROC8a, PROC10, PROC13, PROC19	---	Inhalation	250ppm	0,50
PROC5, PROC8a	---	Dermal	13,71mg/kg/day	0,07
PROC7	with local exhaust ventilation, (95% efficiency)	Inhalation	25ppm	0,05
PROC7	---	Dermal	2,14mg/kg/day	0,01
PROC7	---	Inhalation	350ppm	0,70
PROC7	Outdoor use., 30% efficiency	Dermal	42,86mg/kg/day	0,23
PROC7	half mask	Inhalation	50ppm	0,10
PROC8b	---	Inhalation	150ppm	0,30

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

PROC8b	---	Dermal	6,86mg/kg/day	0,037
PROC9	---	Inhalation	200ppm	0,40
PROC10	---	Dermal	27,43mg/kg/day	0,15
PROC13	---	Dermal	13,71mg/kg/day	0,074
PROC19	with gloves	Dermal	28,29mg/kg/day	0,15

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 11: Use in Cleaning Agents

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC3: Air care products PC4: Anti-freeze and de-icing products PC9a: Coatings and paints, thinners, paint removers PC9b: Fillers, putties, plasters, modelling clay PC9c: Finger paints PC24: Lubricants, greases, release products PC35: Washing and cleaning products (including solvent based products) PC38: Welding and soldering products (with flux coatings or flux cores), flux products
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

### 2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling consumer exposure for: PC3: Aircare, instant action (aerosol sprays)

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	spray aerosol
Amount used	Amount used per event	0,1 g
Frequency and duration of use	Exposure duration	0,25 h
	Frequency of use	365 days/year
	Frequency of use	4 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 6600 cm <sup>2</sup>



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.3 Contributing scenario controlling consumer exposure for: PC3: Aircare, continuous action (solid &amp; liquid)</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 1%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
	Physical Form (at time of use)	solid
Amount used	Amount used per event	0,48 g
Frequency and duration of use	Exposure duration	8 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,70 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.4 Contributing scenario controlling consumer exposure for: PC4: Washing car window</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers product concentrations up to 1%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	0,5 g
Frequency and duration of use	Exposure duration	0,02 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use in a one car garage (34 m3) under typical ventilation.	
<b>2.5 Contributing scenario controlling consumer exposure for: PC4: Pouring into radiator</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	2000 g
Frequency and duration of use	Exposure duration	0,17 h
	Frequency of use	365 days/year

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use in a one car garage (34 m3) under typical ventilation.	
<b>2.6 Contributing scenario controlling consumer exposure for: PC4: Lock de-icer</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	4 g
Frequency and duration of use	Exposure duration	0,25 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 214,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use in a one car garage (34 m3) under typical ventilation.	
<b>2.7 Contributing scenario controlling consumer exposure for: PC9a: Waterborne latex wall paint</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 1,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	2760 g
Frequency and duration of use	Exposure duration	2,2 h
	Frequency of use	4 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.8 Contributing scenario controlling consumer exposure for: PC9a: Solvent rich, high solid, water borne paint</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 27,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	744 g

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

Frequency and duration of use	Exposure duration	2,2 h
	Frequency of use	6 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.9 Contributing scenario controlling consumer exposure for: PC9a: Aerosol spray can</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	spray aerosol
Amount used	Amount used per event	215 g
Frequency and duration of use	Exposure duration	0,33 min
	Frequency of use	2 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 6600 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use in a one car garage (34 m3) under typical ventilation.	
<b>2.10 Contributing scenario controlling consumer exposure for: PC9a: Removers (paint-, glue-, wall paper-, sealant-remover)</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	491 g
Frequency and duration of use	Exposure duration	2 h
	Frequency of use	3 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.11 Contributing scenario controlling consumer exposure for: PC9b: Fillers and putty</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
R51389 / Version 6.0		
59/97		
EN		

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

Amount used	Amount used per event	85 g
Frequency and duration of use	Exposure duration	4 h
	Frequency of use	12 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35,73 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.12 Contributing scenario controlling consumer exposure for: PC9b: Plasters and floor equalizers</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	13800 g
Frequency and duration of use	Exposure duration	2 h
	Frequency of use	12 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.13 Contributing scenario controlling consumer exposure for: PC9b: Modelling clay</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers product concentrations up to 1%
	Physical Form (at time of use)	solid
Amount used	Amount used per event	1 g
Frequency and duration of use	Exposure duration	8 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 254,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.14 Contributing scenario controlling consumer exposure for: PC9c: Finger paints</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	1,35 g
Frequency and duration of use	Exposure duration	8 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 254,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	Avoid using at a product concentration greater than 5%
<b>2.15 Contributing scenario controlling consumer exposure for: PC24: Liquids</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 100%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	2200 g
Frequency and duration of use	Exposure duration	0,17 h
	Frequency of use	4 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use in a one car garage (34 m3) under typical ventilation.	
<b>2.16 Contributing scenario controlling consumer exposure for: PC24: Pastes</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	34 g
Frequency and duration of use	Exposure duration	8 h
	Frequency of use	10 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm <sup>2</sup>
Other given operational conditions affecting consumers	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient	
R51389 / Version 6.0		
61/97		
EN		

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

exposure	temperatures.	
<b>2.17 Contributing scenario controlling consumer exposure for: PC24: Sprays</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	spray aerosol
Amount used	Amount used per event	73 g
Frequency and duration of use	Exposure duration	0,17 h
	Frequency of use	6 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428,75 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.18 Contributing scenario controlling consumer exposure for: PC35: Laundry and dish washing products</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 5 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	15 g
Frequency and duration of use	Exposure duration	0,5 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.19 Contributing scenario controlling consumer exposure for: PC35: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners )</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 5 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	27 g
Frequency and duration of use	Exposure duration	0,33 h
	Frequency of use	128 days/year
	Frequency of use	1 Times per day

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857,5 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
<b>2.20 Contributing scenario controlling consumer exposure for: PC38</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	12 g
Frequency and duration of use	Exposure duration	1 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 6600 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	20 m <sup>3</sup>
	Covers use under typical household ventilation., Covers use at ambient temperatures.	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Consumers

#### Consumers

No exposure assessment presented for human health.

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Risk characterization ratios (RCRs) were calculated by comparing the predicted exposure levels with the corresponding DNELs (derived no effect levels) (RCR = exposure level/DNEL)



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 12: Use in Cleaning Agents

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC19: Hand-mixing with intimate contact and only PPE available</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

### 2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC19

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3)	
	Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC5, PROC8a)	
	or Avoid carrying out operation for more than 4 hours.(PROC5, PROC8a)	
	Ensure material transfers are under containment or extract ventilation. or Limit the substance content in the mixture to 25 %.(PROC10)	
	or Avoid carrying out operation for more than 4 hours.(PROC10)	
	Ensure material transfers are under containment or extract ventilation. or Limit the substance content in the mixture to 25 %. Ensure operation is undertaken outdoors. Avoid carrying out operation for more than 4 hours.(PROC11)	
	or Avoid carrying out operation for more than 1 hour.(PROC11)	
	Avoid carrying out operation for more than 1 hour.(PROC19)	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
	If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A filter or better.(PROC11)	
	If above technical/organisational control measures are not feasible, then adopt following PPE: Limit the substance content in the mixture to 25 %. Wear suitable gloves tested to EN374.(PROC19)	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3	---	Inhalation	100ppm	0,20
PROC4,	---	Inhalation	250ppm	0,50

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

### ACETONE R BULK

PROC8b, PROC9, PROC13				
PROC4, PROC8b, PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC5	---	Dermal	0,07mg/kg/day	0,00
PROC8b	---	Inhalation	350ppm	0,70
PROC5, PROC8a, PROC13	---	Dermal	13,71mg/kg/day	0,07
PROC5, PROC8a	during 1 - 4 hours	Inhalation	300ppm	0,60
PROC5, PROC8a, PROC10	with local exhaust ventilation, 80% efficiency	Inhalation	100ppm	0,20
PROC5	Outdoor use., 30% efficiency	Inhalation	350ppm	0,70
PROC8a	---	Dermal	0,14mg/kg/day	0,001
PROC10	---	Dermal	1,37mg/kg/day	0,007
PROC10	Concentration of substance in product: 5% - 25%	Dermal	16,46mg/kg/day	0,09
PROC10	---	Dermal	27,43mg/kg/day	0,15
PROC11	during 15 mins - 1 hour, with local exhaust ventilation, 80% efficiency	Inhalation	200ppm	0,40
PROC11	---	Dermal	2,14mg/kg/day	0,01
PROC11	during 1 - 4 hours, Concentration of substance in product: 5% - 25%, Outdoor use., 30% efficiency	Inhalation	252ppm	0,50
PROC11	Concentration of substance in product: 5% - 25%	Dermal	64,28mg/kg/day	0,35
PROC11	---	Dermal	107,14mg/kg/day	0,58
PROC11	---	Inhalation	300ppm	0,60
PROC11	half mask	Inhalation	100ppm	0,20
PROC19	Concentration of substance in product: 5% - 25%, with gloves	Dermal	16,97mg/kg/day	0,09
PROC19	Concentration of substance in product: 5% - 25%	Inhalation	300ppm	0,60

#### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### **Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 13: Use as binders and release agents

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure          PROC2: Use in closed, continuous process with occasional controlled exposure          PROC3: Use in closed batch process (synthesis or formulation)          PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises          PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)          PROC6: Calendering operations          PROC7: Industrial spraying          PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities          PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities          PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)          PROC10: Roller application or brushing          PROC13: Treatment of articles by dipping and pouring</p>
Environmental Release Categories	ERC5: Industrial use resulting in inclusion into or onto a matrix

### 2.1 Contributing scenario controlling environmental exposure for: ERC5

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3)	
	Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC7)	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
	If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A filter or better.(PROC7)	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3, PROC4	---	Inhalation	100ppm	0,20
PROC4, PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC5, PROC6, PROC8a	---	Inhalation	250ppm	0,50
PROC5	---	Dermal	13,71mg/kg/day	0,07
PROC6	---	Dermal	27,43mg/kg/day	0,15
PROC7	with local exhaust ventilation, (95% efficiency)	Inhalation	25ppm	0,05
PROC7	---	Dermal	2,14mg/kg/day	0,01
PROC7	---	Inhalation	350ppm	0,70
PROC7	---	Dermal	42,86mg/kg/day	0,23
PROC7	half mask	Inhalation	50ppm	0,10
PROC8a	---	Dermal	13,71mg/kg/day	0,07
PROC8b	---	Inhalation	150ppm	0,30
PROC8b	---	Dermal	6,86mg/kg/day	0,037
PROC9	---	Inhalation	200ppm	0,40

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

PROC10	---	Inhalation	250ppm	0,50
PROC10	---	Dermal	27,34mg/kg/day	0,15
PROC13	---	Inhalation	250ppm	0,50
PROC13	---	Dermal	13,71mg/kg/day	0,074

### **4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### **Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

**ACETONE R BULK**

**1. Short title of Exposure Scenario 14: Use as binders and release agents**

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure          PROC2: Use in closed, continuous process with occasional controlled exposure          PROC3: Use in closed batch process (synthesis or formulation)          PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises          PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)          PROC6: Calendering operations          PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities          PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities          PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)          PROC10: Roller application or brushing          PROC11: Non industrial spraying</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems          ERC8b: Wide dispersive indoor use of reactive substances in open systems          ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix          ERC8d: Wide dispersive outdoor use of processing aids in open systems          ERC8e: Wide dispersive outdoor use of reactive substances in open systems          ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix</p>

**2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8b, ERC8c, ERC8d, ERC8e, ERC8f**

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC11**

Product characteristics	Concentration of the	Covers percentage substance in the product up to
-------------------------	----------------------	--

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Substance in Mixture/Article	100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3)	
	Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC5, PROC8a)	
	or Avoid carrying out operation for more than 4 hours.(PROC5, PROC8a)	
	Ensure operation is undertaken outdoors. or Avoid carrying out operation for more than 4 hours.(PROC6)	
	Ensure material transfers are under containment or extract ventilation. or Limit the substance content in the mixture to 25 %.(PROC10)	
	or Avoid carrying out operation for more than 4 hours.(PROC10)	
	Ensure material transfers are under containment or extract ventilation. or Limit the substance content in the mixture to 25 %. Ensure operation is undertaken outdoors. Avoid carrying out operation for more than 4 hours.(PROC11)	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
	If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A filter or better.(PROC11)	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

PROC3, PROC8b	---	Inhalation	100ppm	0,20
PROC4	---	Inhalation	250ppm	0,50
PROC4	---	Dermal	6,86mg/kg/day	0,04
PROC5	---	Dermal	0,07mg/kg/day	0,00
PROC5, PROC8a	Outdoor use., 30% efficiency	Inhalation	350ppm	0,70
PROC5, PROC8a	---	Dermal	13,71mg/kg/day	0,07
PROC5, PROC8a	during 1 - 4 hours	Inhalation	300ppm	0,60
PROC6	Outdoor use., 30% efficiency	Inhalation	420ppm	0,84
PROC6	---	Dermal	27,43mg/kg/day	0,15
PROC6	during 1 - 4 hours	Inhalation	360ppm	0,72
PROC8a	---	Dermal	0,14mg/kg/day	0,001
PROC8a	---	Dermal	13,71mg/kg/day	0,50
PROC8b	---	Inhalation	250ppm	0,50
PROC8b	---	Dermal	6,86mg/kg/day	0,04
PROC9	---	Inhalation	250ppm	0,50
PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC11	half mask	Inhalation	100ppm	0,20
PROC10	---	Dermal	1,37mg/kg/day	0,007
PROC10	during 1 - 4 hours, Concentration of substance in product: 5% - 25%	Inhalation	300ppm	0,60
PROC10	Concentration of substance in product: 5% - 25%	Dermal	16,46mg/kg/day	0,09
PROC10	---	Dermal	27,43mg/kg/day	0,15
PROC11	during 15 mins - 1 hour, with local exhaust ventilation, 80% efficiency	Inhalation	200ppm	0,40
PROC11	---	Dermal	2,14mg/kg/day	0,01
PROC11	during 1 - 4 hours, Concentration of substance in product: 5% - 25%, Outdoor use., 30% efficiency	Inhalation	252ppm	0,50
PROC11	Concentration of substance in product: 5% - 25%	Dermal	64,28mg/kg/day	0,35
PROC11	---	Dermal	107,14mg/kg/day	0,58
PROC5, PROC10	with local exhaust ventilation, 80% efficiency	Inhalation	100ppm	0,20

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

### **4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template  
(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### **Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 15: Use in agrochemicals

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC11: Non industrial spraying PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

### 2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13, PROC19

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors,	

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	<p>windows etc. Controlled ventilation means air is supplied or removed by a powered fan.</p> <p>Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2)</p> <p>Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC8a)</p> <p>or Avoid carrying out operation for more than 4 hours.(PROC8a)</p> <p>Ensure material transfers are under containment or extract ventilation. or Limit the substance content in the mixture to 25 %. Ensure operation is undertaken outdoors. Avoid carrying out operation for more than 4 hours.(PROC11)</p> <p>or Avoid carrying out operation for more than 1 hour.(PROC11)</p> <p>Avoid carrying out operation for more than 1 hour.(PROC19)</p>
Conditions and measures related to personal protection, hygiene and health evaluation	<p>Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.</p> <p>If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A filter or better.(PROC11)</p> <p>If above technical/organisational control measures are not feasible, then adopt following PPE: Limit the substance content in the mixture to 25 %. Wear suitable gloves tested to EN374.(PROC19)</p>

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1	---	Dermal	0,34mg/kg/day	0,002
PROC2	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC4, PROC8b, PROC13	---	Inhalation	250ppm	0,50
PROC4, PROC8b	---	Dermal	6,86mg/kg/day	0,04
PROC8a	with local exhaust ventilation, 80% efficiency	Inhalation	100ppm	0,20
PROC8a	---	Dermal	0,14mg/kg/day	0,001
PROC8a	Outdoor use., 30% efficiency	Inhalation	350ppm	0,70

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

PROC8a, PROC13	---	Dermal	13,71mg/kg/day	0,07
PROC8a	during 1 - 4 hours	Inhalation	300ppm	0,60
PROC11	during 15 mins - 1 hour, with local exhaust ventilation, 80% efficiency	Inhalation	200ppm	0,40
PROC11	---	Dermal	2,14mg/kg/day	0,01
PROC11	during 1 - 4 hours, Concentration of substance in product: 5% - 25%, Outdoor use., 30% efficiency	Inhalation	252ppm	0,50
PROC11	Concentration of substance in product: 5% - 25%	Dermal	64,28mg/kg/day	0,35
PROC11	---	Dermal	107,14mg/kg/day	0,58
PROC11	half mask	Inhalation	100ppm	0,20
PROC19	Concentration of substance in product: 5% - 25%	Dermal	16,97mg/kg/day	0,09
PROC19	Concentration of substance in product: 5% - 25%	Inhalation	300ppm	0,60

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 16: Use in laboratories

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC10: Roller application or brushing PROC15: Use as laboratory reagent PROC19: Hand-mixing with intimate contact and only PPE available
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

#### 2.1 Contributing scenario controlling environmental exposure for: ERC4

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

#### 2.2 Contributing scenario controlling worker exposure for: PROC10, PROC15, PROC19

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC10, PROC19	---	Inhalation	250ppm	0,50
PROC10	---	Dermal	27,43mg/kg/day	0,15
PROC15	---	Inhalation	50ppm	0,10
PROC15	---	Dermal	0,34mg/kg/day	0,00
PROC19	with gloves	Dermal	28,29mg/kg/day	0,15

#### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

##### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

##### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 17: Use in laboratories

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC10: Roller application or brushing PROC15: Use as laboratory reagent PROC19: Hand-mixing with intimate contact and only PPE available
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems

### 2.1 Contributing scenario controlling environmental exposure for: ERC8a

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC10, PROC15, PROC19

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Ensure material transfers are under containment or extract ventilation. or Limit the substance content in the mixture to 25 %.(PROC10)	
	or Avoid carrying out operation for more than 4 hours.(PROC10)	
	Avoid carrying out operation for more than 1 hour.(PROC19)	
Conditions and measures related	Use suitable eye protection.	



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

to personal protection, hygiene  
and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

If above technical/organisational control measures are not feasible, then adopt following PPE:

Limit the substance content in the mixture to 25 %.

Wear suitable gloves tested to EN374.(PROC19)

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC10	with local exhaust ventilation, 80% efficiency	Inhalation	100ppm	0,20
PROC10	---	Dermal	1,37mg/kg/day	0,007
PROC15	---	Inhalation	50ppm	0,10
PROC15	---	Dermal	0,34mg/kg/day	0,002
PROC19	Concentration of substance in product: 5% - 25%	Inhalation	300ppm	0,60
PROC19	Concentration of substance in product: 5% - 25%, with gloves	Dermal	16,97mg/kg/day	0,09

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 18: Use as blowing agents

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC12: use of blowing agents in manufacture of foam
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles ERC10a: Wide dispersive outdoor use of long-life articles and materials with low release

#### 2.1 Contributing scenario controlling environmental exposure for: ERC4, ERC10a

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

#### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3)
--	--

Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
---	---

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3, PROC12	---	Inhalation	100ppm	0,20
PROC8b	---	Inhalation	150ppm	0,30
PROC8b	---	Dermal	6,86mg/kg/day	0,037
PROC9	---	Inhalation	200ppm	0,40
PROC9	---	Dermal	6,86mg/kg/day	0,04
PROC12	---	Dermal	0,34mg/kg/day	0,00

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template (<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 19: Use in de-icing and anti-icing applications

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC4: Anti-freeze and de-icing products
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems

#### 2.1 Contributing scenario controlling environmental exposure for: ERC8d

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

#### 2.2 Contributing scenario controlling consumer exposure for: PC4: Washing car window

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 1 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	0,5 g
Frequency and duration of use	Exposure duration	0,02 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 6600 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	

#### 2.3 Contributing scenario controlling consumer exposure for: PC4: Pouring into radiator

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 10%
-------------------------	---	---------------------------------

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	2000 g
Frequency and duration of use	Exposure duration	0,17 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	
<b>2.4 Contributing scenario controlling consumer exposure for: PC4: Lock de-icer</b>		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	240 hPa
Amount used	Amount used per event	4 g
Frequency and duration of use	Exposure duration	0,25 h
	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 214,4 cm <sup>2</sup>
Other given operational conditions affecting consumers exposure	Room size	34 m <sup>3</sup>
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.	

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Consumers

#### Consumers

No exposure assessment presented for human health.

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

### Health

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Risk characterization ratios (RCRs) were calculated by comparing the predicted exposure levels with the corresponding DNELs (derived no effect levels) ( $RCR = \text{exposure level}/\text{DNEL}$ )

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 20: Use in de-icing and anti-icing applications

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC11: Non industrial spraying PROC19: Hand-mixing with intimate contact and only PPE available
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems

#### 2.1 Contributing scenario controlling environmental exposure for: ERC8d

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

#### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC8b, PROC11, PROC19

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2)	
	Ensure material transfers are under containment or extract ventilation.	

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	or Limit the substance content in the mixture to 25 %. Ensure operation is undertaken outdoors. Avoid carrying out operation for more than 4 hours.(PROC11)
	or Avoid carrying out operation for more than 1 hour.(PROC11)
	Avoid carrying out operation for more than 1 hour.(PROC19)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
	If above technical/organisational control measures are not feasible, then adopt following PPE: Wear a respirator conforming to EN140 with Type A filter or better.(PROC11)
	If above technical/organisational control measures are not feasible, then adopt following PPE: Limit the substance content in the mixture to 25 %. Wear suitable gloves tested to EN374.(PROC19)

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

##### ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1	---	Dermal	0,34mg/kg/day	0,002
PROC2	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,10
PROC8b	---	Inhalation	250ppm	0,50
PROC8b	---	Dermal	6,86mg/kg/day	0,04
PROC11	during 15 mins - 1 hour, with local exhaust ventilation, 80% efficiency	Inhalation	200ppm	0,40
PROC11	---	Dermal	2,14mg/kg/day	0,01
PROC11	during 1 - 4 hours, Concentration of substance in product: 5% - 25%, Outdoor use., 30% efficiency	Inhalation	252ppm	0,50
PROC11	Concentration of substance in product: 5% - 25%	Dermal	64,28mg/kg/day	0,35
PROC11	---	Dermal	107,14mg/kg/day	0,58
PROC11	half mask	Inhalation	100ppm	0,20
PROC19	Concentration of substance in product: 5% - 25%	Inhalation	300ppm	0,60



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

PROC19	Concentration of substance in product: 5% - 25%, with gloves	Dermal	16,97mg/kg/day	0,09
--------	--	--------	----------------	------

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 21: Use in Oil and Gas field drilling and production operations

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

#### 2.1 Contributing scenario controlling environmental exposure for: ERC4

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

#### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure.	

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

Handle substance within a closed system.(PROC1, PROC2, PROC3)

Conditions and measures related to personal protection, hygiene and health evaluation  
Use suitable eye protection.  
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3, PROC4	---	Inhalation	100ppm	0,20
PROC4	---	Dermal	6,86mg/kg/day	0,04
PROC8a	---	Inhalation	250ppm	0,50
PROC8a	---	Dermal	13,71 mg/kg/day	0,07
PROC8b	---	Inhalation	150ppm	0,30
PROC8b	---	Dermal	6,86mg/kg/day	0,037

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template (<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 22: Use in Oil and Gas field drilling and production operations

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems

#### 2.1 Contributing scenario controlling environmental exposure for: ERC8d

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

#### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.(PROC1, PROC2, PROC3) or Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC8a) or Avoid carrying out operation for more than 4 hours.(PROC8a)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC2	---	Inhalation	50ppm	0,10
PROC2	---	Dermal	1,37mg/kg/day	0,01
PROC3	---	Inhalation	100ppm	0,20
PROC4, PROC8b	---	Inhalation	250ppm	0,50
PROC4, PROC8b	---	Dermal	6,86mg/kg/day	0,04
PROC8a	---	Dermal	0,14mg/kg/day	0,001
PROC8a	Outdoor use., 30% efficiency	Inhalation	350ppm	0,70
PROC8a	---	Dermal	13,71mg/kg/day	0,07
PROC8a	during 1 - 4 hours	Inhalation	300ppm	0,60
PROC8a	with local exhaust ventilation, 80% efficiency	Inhalation	100ppm	0,20

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## **ACETONE R BULK**

(<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### **Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

### 1. Short title of Exposure Scenario 23: Explosives manufacture & use

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC3: Use in closed batch process (synthesis or formulation) PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems

### 2.1 Contributing scenario controlling environmental exposure for: ERC8d

Substance is a unique structure, Readily biodegradable.

Amount used	To be defined by site	
Frequency and duration of use	Continuous exposure	360 days/year
Other given operational conditions affecting environmental exposure	Indoor/Outdoor use.	
Technical conditions and measures at process level (source) to prevent release Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Organizational measures to prevent/limit release from the site	Air	Treat air emission to provide a typical removal efficiency of (%): (Efficiency: 90 %)
	Air	Closed system, or, Treated by scrubbers
	Air	or, Charcoal adsorbers
	Common practices vary across sites thus conservative process release estimates used.	
Conditions and measures related to external treatment of waste for disposal	Contain and dispose of waste in accordance with environmental legislation and according to local regulations.	
Conditions and measures related to external recovery of waste	If recycling is not practicable, dispose of in compliance with local regulations.	

### 2.2 Contributing scenario controlling worker exposure for: PROC1, PROC3, PROC5, PROC8a, PROC8b

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	> 10 kPa
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently).	
Technical conditions and measures to control dispersion from source towards the worker	Locate bulk storage outdoors. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.	
	Sample via a closed loop or other system to avoid exposure.	

{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sap  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ACETONE R BULK

	Handle substance within a closed system.(PROC1, PROC3) Ensure material transfers are under containment or extract ventilation. or Ensure operation is undertaken outdoors.(PROC5, PROC8a) or Avoid carrying out operation for more than 4 hours.(PROC5, PROC8a)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### 3. Exposure estimation and reference to its source

#### Environment

No information available.

#### Workers

ECETOC TRA

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	---	Inhalation	0,01ppm	0,00002
PROC1, PROC3	---	Dermal	0,34mg/kg/day	0,002
PROC3, PROC5	---	Inhalation	100ppm	0,20
PROC5	---	Dermal	0,07mg/kg/day	0,00
PROC5	---	Inhalation	350ppm	0,70
PROC5	---	Dermal	13,71mg/kg/day	0,07
PROC5	---	Inhalation	300ppm	0,60
PROC8a	---	Dermal	0,14mg/kg/day	0,001
PROC8a	---	Dermal	13,71mg/kg/day	0,07
PROC8a	with local exhaust ventilation, 80% efficiency	Inhalation	100ppm	0,20
PROC8a	Outdoor use., 30% efficiency	Inhalation	350ppm	0,70
PROC8a	during 1 - 4 hours	Inhalation	300ppm	0,60

### 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

#### Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see ECT Tool:

ECT: <http://www.reachcentrum.eu/en/consortiummanagement/consortia-under-reach/phenol-derivatives-reachconsortium/phenol-derivatives-dossiers.aspx>

#### Health

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

For scaling see: GES Worker Chemical Safety Assessment (CSA) Template (<http://cefic.org/templates/shwPublications.asp?HID=750>)

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



{ error: file not found:  
C:\Program Files  
(x86)\SAP\FrontEnd\sapg  
ui\WWI\graphics\Connecti  
ngChemistry.jpg }

{ error: graphic file not  
found: C:\Program Files  
(x86)\SAP\FrontEnd\sap  
gui\WWI\graphics\brennt  
ag.bmp }

## ***ACETONE R BULK***

### **Additional good practice advice beyond the REACH Chemical Safety Assessment**

Assumes a good basic standard of occupational hygiene is implemented.